

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number
WO 2005/083467 A1

(51) International Patent Classification⁷: **G01V 3/28**

(21) International Application Number:
PCT/GB2004/000724

(22) International Filing Date: 23 February 2004 (23.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **OXFORD GEOSERVICE LIMITED** [GB/GB]; PLLG, Suite 23, 6-8 York Place, Leeds LS1 2DS (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ZHDANOV, Michael** [GB/GB]; Oxford Geoservice Limited, PLLG, Suite 23, 6-8 York Place, Leeds LS1 2DS (GB).

(74) Agent: **BAILEY WALSH & CO LLP**; 5 York Place, Leeds LS1 2SD (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR GRADIENT ELECTROMAGNETIC INDUCTION WELL LOGGING



(57) Abstract: The method and apparatus for determining the conductivity of anisotropic formations surrounding a borehole. The method comprises measuring the gradient of the magnetic field by an electromagnetic logging tool in a borehole in the subsurface formation. The instrument comprises one or several closely positioned parallel receiver coils and one or several closely positioned parallel transmitter coils with the magnetic moment direction of the transmitter coils parallel or different from the magnetic moment direction of the receiver coils. In a preferred embodiment a gradient induction instrument consists of a tri-axial transmitter array and up to 27 pairs of receiver coils, measuring some or all magnetic gradient components: formula (I).

WO 2005/083467 A1